

UT Spot Track Ø 86

09.4286.30 - White


Spotlight to be installed on 3-phase track, with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	CRI	98
Lamp category	LED	Net lumen (lm)	1822
Power (W)	34.1W	Mountings	Track
System power (W)	34.1	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle:	17°	
<u>h(m)</u>	<u>E(lx)</u>	<u>D(m)</u>
1	22114	0.30
2	5528	0.59
3	2457	0.89
4	1382	1.18
5	885	1.48

Luminous flux luminaire
3248 lm

Electrical

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	220-240V	Emergency	Without
Current (mA)	1050	Insulation class	II
Dimmable	No		
Driver	Integrated		

Physical

Color	White	Spot diameter (mm) 86
Orientation	Adjustable	
Weight (kg)	1.36	
Tilt (°)	90	
Rotation (°)	360	

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø 86



Screening crosspiece
08.8411.00

Holding ring
08.8410.00