

## UT Spot Track Ø 86

09.4287.30A - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1995
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	34.1W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	23
<b>Beam angle C90-270 (°)</b>	23



Beam Angle: 23°

h(m)	E(lx)	D(m)
1	9271	0.41
2	2318	0.82
3	1030	1.23
4	579	1.64
5	371	2.05

Luminous flux luminaire  
1995 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	86
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	1.36		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note


FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

## UT Spot Track Ø 86



---

Screening crosspiece  
08.8411.00



---

Holding ring  
08.8410.00