

## UT Spot Track Ø 86

09.4887.30A - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2089
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	33W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	24
<b>Beam angle C90-270 (°)</b>	24



Beam Angle: 24°

	h(m)	E(lx)	D(m)
1	9482	0.43	
2	2370	0.86	
3	1054	1.28	
4	593	1.71	
5	379	2.14	


Luminous flux luminaire  
2089 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.75
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	360



### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

## UT Spot Track Ø 86



---


Elliptical lens  
08.8163.68

---

Screening crosspiece  
08.8411.00

---

Honeycomb  
08.8495.14



---

Flood lens  
08.8175.68

---

Holding ring  
08.8410.00