

## UT Spot Track Ø 86

■ 09.4888.14A - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1991
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	32.8W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	37
<b>Beam angle C90-270 (°)</b>	37



<b>Beam Angle:</b>	37°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	5566	0.67	
2	1392	1.34	
3	618	2.01	
4	348	2.69	
5	223	3.36	

Luminous flux luminaire  
1991 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.75
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	360

### Note


FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

## UT Spot Track Ø 86



---

Elliptical lens  
08.8163.68



---

Holding ring  
08.8410.00



---

Screening crosspiece  
08.8411.00



---

Honeycomb  
08.8495.14



---

Flood lens  
08.8175.68