



UT Spot Track Ø 86 Dali Version

■ 09.4244.14ADA - Black


Spotlight to be installed on 3-phase track. With LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	1836
Lamp category	LED	Mountings	Track
Power (W)	34.1W	Environment	Indoor
CCT (K)	3000K		
CRI	98		

Optical


Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle: 23°

h(m)	E(lx)	D(m)
1	9271	0.41
2	2318	0.82
3	1030	1.23
4	579	1.64
5	371	2.05

Luminous flux luminaire
1995 lm



Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable DALI		

Physical


Color	Black	Spot diameter (mm)	86
Orientation	Adjustable		
Weight (kg)	1.36		
Tilt (°)	90		
Rotation (°)	360		

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.



UT Spot Track Ø 86 Dali Version



Holding ring
08.8410.00



Screening crosspiece
08.8411.00