



UT Spot Track Ø 86 Dali Version

■ 09.4841.14ADA - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	CRI	80
Lamp category	LED	Net lumen (lm)	2528
Power (W)	32.8	Mountings	Track
System power (W)	32.8	Environment	Indoor dry location
CCT (K)	3000K		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	24
Beam angle C90-270 (°)	24



Beam Angle: 24°

	h(m)	E(lx)	D(m)
1	11472	0.43	
2	2868	0.86	
3	1275	1.28	
4	717	1.71	
5	459	2.14	

Luminous flux luminaire
2528 lm



Electrical


Frequency (Hz)	50/60	Driver type	Dimmable DALI 1
Voltage (V)	220-240V	Emergency	Without
Current (mA)	900	Insulation class	II
Dimmable	Yes		
Driver	Integrated		

Physical

Color	Black	Spot diameter (mm)	86
Orientation	Adjustable		
Weight (kg)	0.74		
Tilt (°)	90		
Rotation (°)	360		

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.



UT Spot Track Ø 86 Dali Version



Honeycomb
08.8495.14



Flood lens
08.8175.68



Holding ring
08.8410.00



Elliptical lens
08.8163.68



Screening crosspiece
08.8411.00