



UT Spot Track Ø 86 Dali Version

■ 09.4844.14ADA - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

| | | | |
|------------------------|-------|-----------------------|--------|
| Number of heads | 1 | Net lumen (lm) | 2089 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 33W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical


| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 24 |
| Beam angle C90-270 (°) | 24 |



Beam Angle: 24°

| | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 9482 | 0.43 | |
| 2 | 2370 | 0.86 | |
| 3 | 1054 | 1.28 | |
| 4 | 593 | 1.71 | |
| 5 | 379 | 2.14 | |

Luminous flux luminaire
2089 lm



Electrical


| | | | |
|-----------------------|--------------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Electronic dimmable DALI | | |

Physical

| | |
|---------------------|------------|
| Color | Black |
| Orientation | Adjustable |
| Weight (kg) | 1.18 |
| Tilt (°) | 90 |
| Rotation (°) | 360 |

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.



UT Spot Track Ø 86 Dali Version



Holding ring
08.8410.00



Screening crosspiece
08.8411.00



Elliptical lens
08.8163.68



Flood lens
08.8175.68



Honeycomb
08.8495.14