



UT Spot Track Ø 86 Dali Version

■ 09.4845.14ADA - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	1991
Lamp category	LED	Mountings	Track
Power (W)	32.8W	Environment	Indoor
CCT (K)	3000K		
CRI	90		


Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	37
Beam angle C90-270 (°)	37



Beam Angle:	37°		
	h(m)	E(lx)	D(m)
1	5566	0.67	
2	1392	1.34	
3	618	2.01	
4	348	2.69	
5	223	3.36	

Luminous flux luminaire
1991 lm



Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable DALI		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	1.18
Tilt (°)	90
Rotation (°)	360

Note


FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.



UT Spot Track Ø 86 Dali Version



Elliptical lens
08.8163.68



Holding ring
08.8410.00



Screening crosspiece
08.8411.00



Honeycomb
08.8495.14



Flood lens
08.8175.68