



## UT Spot Track Ø 86 GA

■ 09.7732.14 - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 80                  |
| Lamp category    | LED   | Net lumen (lm) | 1947                |
| Power (W)        | 27    | Mountings      | Track               |
| System power (W) | 29.3  | Environment    | Indoor dry location |
| CCT (K)          | 4000K |                |                     |

### Optical

|                        |              |
|------------------------|--------------|
| Lighting type          | Direct       |
| LED type               | Phosphor LED |
| Light distribution     | Symmetric    |
| Optical type           | Flood        |
| Beam angle (°)         | 32           |
| Beam angle C90-270 (°) | 32           |



Beam Angle: 32°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 5719 | 0.58  |      |
| 2 | 1430 | 1.15  |      |
| 3 | 635  | 1.73  |      |
| 4 | 357  | 2.31  |      |
| 5 | 229  | 2.89  |      |

Luminous flux luminaire  
1947 lm



### Electrical



|                |            |                  |              |
|----------------|------------|------------------|--------------|
| Frequency (Hz) | 50/60      | Driver type      | Non Dimmable |
| Voltage (V)    | 220-240V   | Emergency        | Without      |
| Current (mA)   | 900        | Insulation class | II           |
| Dimmable       | No         |                  |              |
| Driver         | Integrated |                  |              |

### Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | Black      | Spot diameter (mm) | 86 |
| Orientation  | Adjustable |                    |    |
| Weight (kg)  | 0.75       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.



UT Spot Track Ø 86 GA



---

Screening crosspiece  
08.8411.00

---

Holding ring  
08.8410.00