



## UT Spot Track Ø 86 GA Dali Version

■ 09.7751.14ADA - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	Net lumen (lm)	2281
Lamp category	LED	Mountings	Track
Power (W)	33W	Environment	Indoor
CCT (K)	4000K		
CRI	90		

### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12



Beam Angle: 12°

	h(m)	E(lx)	D(m)
1	29396	0.21	
2	7349	0.41	
3	3266	0.62	
4	1837	0.82	
5	1176	1.03	

Luminous flux luminaire  
2281 lm




### Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable DALI		
Emergency	Without		

### Physical


Color	Black	Spot diameter (mm)	86
Orientation	Adjustable		
Weight (kg)	0.75		
Tilt (°)	90		
Rotation (°)	360		



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.

## UT Spot Track Ø 86 GA Dali Version



---

Holding ring  
08.8410.00



---

Screening crosspiece  
08.8411.00



---

Elliptical lens  
08.8163.68



---

Flood lens  
08.8175.68



---

Honeycomb  
08.8495.14