

UT Spot Track Ø 86 On Board Dimmer Included

09.4243.14 - Black

Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	**CRI**	98
Lamp category	LED	**Net lumen (lm)**	1822
Power (W)	31W	**Mountings**	Track
System power (W)	32.9	**Environment**	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Luminous flux luminaire
1648 lm

Beam Angle: 16°

h(m)	E(lx)	D(m)
1	12488	0.28
2	3122	0.55
3	1388	0.83
4	781	1.10
5	500	1.38

Electrical

Frequency (Hz)	50/60	**Driver type**	Dimmer on board
Voltage (V)	220-240V	**Emergency**	Without
Current (mA)	950	**Insulation class**	II
Dimmable	Yes		
Driver	Integrated		

Physical

Color	Black	**Spot diameter (mm)**	86
Orientation	Adjustable		
Weight (kg)	1.36		
Tilt (°)	90		
Rotation (°)	360		

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø 86 On Board Dimmer Included

Screening crosspiece
08.8411.00

Holding ring
08.8410.00