

UT Spot Track Ø 86 On Board Dimmer Included

■ 09.4244.14A - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1836 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 31W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 98 | | |

Optical

| | |
|-------------------------------|--------------|
| Lighting type | Direct |
| LED type | Phosphor LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 23 |
| Beam angle C90-270 (°) | 23 |



Beam Angle: 23°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 8532 | 0.41 |
| 2 | 2133 | 0.82 |
| 3 | 948 | 1.23 |
| 4 | 533 | 1.64 |
| 5 | 341 | 2.05 |

Luminous flux luminaire
1836 lm

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmer on board | | |

Physical

| | | | |
|---------------------|------------|---------------------------|----|
| Color | Black | Spot diameter (mm) | 86 |
| Orientation | Adjustable | | |
| Weight (kg) | 1.36 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø 86 On Board Dimmer Included



Holding ring
08.8410.00



Screening crosspiece
08.8411.00