

UT Spot Track Ø 86 On Board Dimmer Included

09.4251.30A - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	2363
Lamp category	LED	Mountings	Track
Power (W)	29.3W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle:	23°		
h(m)	E(lx)	D(m)	
1	11140	0.41	
2	2785	0.81	
3	1238	1.22	
4	696	1.63	
5	446	2.03	

Luminous flux luminaire
2363 lm

Electrical

Frequency (Hz)	50/60	Driver type	Dimmer on board
Voltage (V)	220	Emergency	Without
Current (mA)	1050	Insulation class	II
Dimmable	Yes		
Driver	Integrated		

Physical

Color	White	Spot diameter (mm)	86
Orientation	Adjustable		
Weight (kg)	1.36		
Tilt (°)	90		
Rotation (°)	360		

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø 86 On Board Dimmer Included



Screening crosspiece
08.8411.00



Holding ring
08.8410.00