

UT Spot Track Ø 86 On Board Dimmer Included

09.4840.30A - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	2650
Lamp category	LED	Mountings	Track
Power (W)	33W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12



Beam Angle:	12°		
	h(m)	E(lx)	D(m)
1	34142	0.21	
2	8535	0.41	
3	3794	0.62	
4	2134	0.82	
5	1366	1.03	

Luminous flux luminaire
2650 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	0.75
Tilt (°)	90
Rotation (°)	360

Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø 86 On Board Dimmer Included



Elliptical lens
08.8163.68



Flood lens
08.8175.68



Screening crosspiece
08.8411.00



Honeycomb
08.8495.14



Holding ring
08.8410.00