

## UT Spot Track Ø 86 On Board Dimmer Included

■ 09.4842.14A - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 2408                |
| Lamp category   | LED   | Mountings      | Track               |
| Power (W)       | 33W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 80    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 37        |
| Beam angle C90-270 (°) | 37        |



|             |      |       |      |
|-------------|------|-------|------|
| Beam Angle: | 37°  |       |      |
|             | h(m) | E(lx) | D(m) |
| 1           | 6735 | 0.67  |      |
| 2           | 1684 | 1.34  |      |
| 3           | 748  | 2.01  |      |
| 4           | 421  | 2.69  |      |
| 5           | 269  | 3.36  |      |

Luminous flux luminaire  
2408 lm

### Electrical

|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 220.00          | Insulation class | II      |
| Dimmable       | Yes             |                  |         |
| Driver         | Integrated      |                  |         |
| Driver type    | Dimmer on board |                  |         |

### Physical

|              |            |
|--------------|------------|
| Color        | Black      |
| Orientation  | Adjustable |
| Weight (kg)  | 0.75       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

## UT Spot Track Ø 86 On Board Dimmer Included




---

Honeycomb  
08.8495.14



---

Screening crosspiece  
08.8411.00



---

Holding ring  
08.8410.00



---

Flood lens  
08.8175.68



---

Elliptical lens  
08.8163.68