

UT Spot Track Ø57

09.4480.30A - White

Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	**Net lumen (lm)**	1255
Lamp category	LED	**Mountings**	Track
Power (W)	21.5W	**Environment**	Indoor
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	21
Beam angle C90-270 (°)	21



Luminous flux luminaire
2007 lm

Beam Angle: 13°

h(m)	E(lx)	D(m)
1	19095	0.22
2	4774	0.44
3	2122	0.66
4	1193	0.88
5	764	1.10

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	220.00	**Insulation class**	II
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	0.57
Tilt (°)	90
Rotation (°)	360

Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø57

Honeycomb
08.8428.00

Flood lens
08.8432.00

Elliptical lens
08.8431.00

Snoot shielding cone
08.0526.00

Snoot shielding cone
08.0526.40

Snoot shielding cone
08.0526.BW

Screening crosspiece
08.8429.00