



## UT Spot Track Ø57

■ 09.4485.14A - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	Net lumen (lm)	1216
Lamp category	LED	Mountings	Track
Power (W)	21.5W	Environment	Indoor
CCT (K)	4000K		
CRI	90		

### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	42
Beam angle C90-270 (°)	42



Beam Angle: 42°

h(m)	E(lx)	D(m)
1	2879	0.76
2	720	1.52
3	320	2.28
4	180	3.05
5	115	3.81

Luminous flux luminaire  
1216 lm




### Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

### Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.57
Tilt (°)	90
Rotation (°)	360



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø57



---

Honeycomb  
08.8428.00

---

Flood lens  
08.8432.00

---

Elliptical lens  
08.8431.00



---

Snoot shielding cone  
08.0526.00

---

Snoot shielding cone  
08.0526.40

---

Snoot shielding cone  
08.0526.BW



---

Screening crosspiece  
08.8429.00