



UT Spot Track Ø57 Dali Version

09.4440.14ADA - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	1255
Lamp category	LED	Mountings	Track
Power (W)	22W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Luminous flux luminaire

Beam Angle:		10°
h(n	n) E(l x)	D(m)
1_	14650	0.18
2	3662	0.36
3	1628	0.54
4	916	0.72
5	586	0.90

1255 lm

Electrical

Frequency (Hz)	50/60	Insulation class
Dimmable	Yes	
Driver	Integrated	
Driver type	Electronic	
	dimmable DALI	

Without

Emergency Physical

,	
Color	Black
Orientation	Adjustable
Weight (kg)	0.57
Tilt (°)	90
Rotation (°)	360



255

Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks $recommended \ by \ FLOS. \ Compatibility \ is \ guaranteed \ with \ three-phase \ track \ produced \ by \ Nordic \ Aluminium.$ $Compatibility\ with\ Eutrac\ under\ request.\ FLOS\ three-phase\ DALI\ track\ luminaires\ are\ designed\ for\ Pulse\ luminaires\ designed\ for\ pulse\ for\ pulse\ pulse$ from Nordic Aluminium.

UT Spot Track Ø57 Dali Version







Honeycomb 08.8428.00 Flood lens 08.8432.00 Elliptical lens 08.8431.00







Snoot shielding cone 08.0526.00

Snoot shielding cone 08.0526.40

Snoot shielding cone 08.0526.BW



Screening crosspiece 08.8429.00