



UT Spot Track Ø57 GA

09.7707.30A - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated. .30 versions come with the track adapter, the arm and the rear of the head in black.

Main specifications

| | | | |
|------------------------|-------|-----------------------|--------|
| Number of heads | 1 | Net lumen (lm) | 941 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 23.5W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 21 |
| Beam angle C90-270 (°) | 21 |




Beam Angle: 21°

h(m) E(lx) D(m)

| | | |
|---|------|------|
| 1 | 5178 | 0.37 |
| 2 | 1294 | 0.73 |
| 3 | 575 | 1.10 |
| 4 | 324 | 1.47 |
| 5 | 207 | 1.83 |

Luminous flux luminaire
941 lm




Electrical

| | | | |
|-----------------------|------------|-------------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Electronic | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|------------|---------------------------|----|
| Color | White | Spot diameter (mm) | 57 |
| Orientation | Adjustable | | |
| Weight (kg) | 0.57 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Certification / Marking



Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.


UT Spot Track Ø57 GA



Honeycomb
08.8428.00



Flood lens
08.8432.00



Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.00



Screening crosspiece
08.8429.00