



## UT Spot Track Ø57 GA All White

09.7707.30A78 - White

Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.


### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	941
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	23.5W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		



### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	21
<b>Beam angle C90-270 (°)</b>	21




Beam Angle: 21°

h(m) E(lx) D(m)

1	5178	0.37
2	1294	0.73
3	575	1.10
4	324	1.47
5	207	1.83

Luminous flux luminaire  
941 lm




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	57
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	0.57		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Certification / Marking



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

## UT Spot Track Ø57 GA All White



---

Honeycomb  
08.8428.00



---

Flood lens  
08.8432.00



---

Elliptical lens  
08.8431.00



---

Snoot shielding cone  
08.0526.00



---

Screening crosspiece  
08.8429.00