



## UT Spot Track Ø57 GA Dali Version

■ 09.7704.14ADA - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 1394   |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 21.5W | Environment    | Indoor |
| CCT (K)         | 3000K |                |        |
| CRI             | 80    |                |        |

### Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 42        |
| Beam angle C90-270 (°) | 42        |



Beam Angle: 42°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 3301  | 0.76 |
| 2    | 825   | 1.52 |
| 3    | 367   | 2.28 |
| 4    | 206   | 3.05 |
| 5    | 132   | 3.81 |

Luminous flux luminaire  
1394 lm




### Electrical

|                |                             |                  |    |
|----------------|-----------------------------|------------------|----|
| Frequency (Hz) | 50/60                       | Insulation class | II |
| Dimmable       | Yes                         |                  |    |
| Driver         | Integrated                  |                  |    |
| Driver type    | Electronic<br>dimmable DALI |                  |    |
| Emergency      | Without                     |                  |    |

### Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | Black      | Spot diameter (mm) | 57 |
| Orientation  | Adjustable |                    |    |
| Weight (kg)  | 0.57       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.

UT Spot Track Ø57 GA Dali Version



---

Honeycomb  
08.8428.00

---

Flood lens  
08.8432.00

---

Elliptical lens  
08.8431.00



---

Snoot shielding cone  
08.0526.00

---

Snoot shielding cone  
08.0526.40

---

Snoot shielding cone  
08.0526.BW



---

Screening crosspiece  
08.8429.00