

UT Spot Track Ø57 On Board Dimmer Included

09.4443.30A - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 997 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 21.5W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 10 |
| Beam angle C90-270 (°) | 10 |



Beam Angle: 10°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 11643 | 0.18 |
| 2 | 2911 | 0.36 |
| 3 | 1294 | 0.54 |
| 4 | 728 | 0.72 |
| 5 | 466 | 0.90 |

Luminous flux luminaire
997 lm

Electrical

| | | | |
|----------------|---------------------|------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Electronic dimmable | | |
| Emergency | Without | | |

Physical

| | |
|--------------|------------|
| Color | White |
| Orientation | Adjustable |
| Weight (kg) | 0.57 |
| Tilt (°) | 90 |
| Rotation (°) | 360 |

Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø57 On Board Dimmer Included



Honeycomb
08.8428.00



Flood lens
08.8432.00



Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.00



Snoot shielding cone
08.0526.40



Snoot shielding cone
08.0526.BW



Screening crosspiece
08.8429.00