

## UT Spot Track Ø57 On Board Dimmer Included

■ 09.4450.14A - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	Net lumen (lm)	1094
Lamp category	LED	Mountings	Track
Power (W)	21.5W	Environment	Indoor
CCT (K)	4000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Beam Angle: 10°

h(m)	E(lx)	D(m)
1	12780	0.18
2	3195	0.36
3	1420	0.54
4	799	0.72
5	511	0.90

Luminous flux luminaire  
1094 lm

### Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable		
Emergency	Without		


### Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.57
Tilt (°)	90
Rotation (°)	360

### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø57 On Board Dimmer Included



---

Honeycomb  
08.8428.00

---

Flood lens  
08.8432.00

---

Elliptical lens  
08.8431.00



---

Snoot shielding cone  
08.0526.00

---

Snoot shielding cone  
08.0526.40

---

Snoot shielding cone  
08.0526.BW



---

Screening crosspiece  
08.8429.00