

## UT Spot Track Ø86

09.4885.30A - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 2074   |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 32.8W | Environment    | Indoor |
| CCT (K)         | 4000K |                |        |
| CRI             | 90    |                |        |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 37        |
| Beam angle C90-270 (°) | 37        |



Beam Angle: 37°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 5799  | 0.67 |
| 2    | 1450  | 1.34 |
| 3    | 644   | 2.01 |
| 4    | 362   | 2.69 |
| 5    | 232   | 3.36 |

Luminous flux luminaire  
2074 lm


### Electrical

|                |            |                  |         |
|----------------|------------|------------------|---------|
| Frequency (Hz) | 50/60      | Emergency        | Without |
| Voltage (V)    | 220.00     | Insulation class | II      |
| Dimmable       | No         |                  |         |
| Driver         | Integrated |                  |         |
| Driver type    | Electronic |                  |         |

### Physical

|              |            |
|--------------|------------|
| Color        | White      |
| Orientation  | Adjustable |
| Weight (kg)  | 0.75       |
| Tilt (°)     | 90         |
| Rotation (°) | 360        |

### Certification / Marking



### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø86



Holding ring  
08.8410.00



Screening crosspiece  
08.8411.00



Elliptical lens  
08.8163.68



Flood lens  
08.8175.68



Honeycomb  
08.8495.14