

UT Spot Track Ø86 Dali Version

09.4252.30.DA - White


Spotlight to be installed on 3-phase track. With LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 1947 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 29.3W | Environment | Indoor |
| CCT (K) | 4000K | | |
| CRI | 80 | | |

Optical

| | |
|------------------------|--------------|
| Lighting type | Direct |
| LED type | Phosphor LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 32 |
| Beam angle C90-270 (°) | 32 |



Beam Angle: 32°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 5719 | 0.58 |
| 2 | 1430 | 1.15 |
| 3 | 635 | 1.73 |
| 4 | 357 | 2.31 |
| 5 | 229 | 2.89 |

Luminous flux luminaire
1947 lm


Electrical

| | | | |
|----------------|----------------------------|------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Electronic dimable DALI | | |
| Emergency | Without | | |

Physical

| | |
|--------------|------------|
| Color | White |
| Orientation | Adjustable |
| Weight (kg) | 1.36 |
| Tilt (°) | 90 |
| Rotation (°) | 360 |

Certification / Marking



Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.

UT Spot Track Ø86 Dali Version



Holding ring
08.8410.00

Screening crosspiece
08.8411.00