Beam Angle:

h(m) = E(Ix)

12488

3122

16°


D(m)

0.28

0.55







09.7733.14.DA - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

Number of heads	1	Net lumen (lm)	1648
Lamp category	LED	Mountings	Track
Power (W)	23.5W	Environment	Indoor
CCT (K)	3000K		
CRI	98		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



1648 lm


3 1388 0.83 4 781 1.10 5 500 1.38 Luminous flux luminaire

Electrical

Frequency (Hz)	50/60	Insulation class
Dimmable	Yes	
Driver	Integrated	
Driver type	Electronic	
	dimmable DALI	
Emergency	Without	

Physical

i riysicai		
Color	Black	Spot diameter (mm) 86
Orientation	Adjustable	
Weight (kg)	0.75	
Tilt (°)	90	
Rotation (°)	360	



\ <u>\</u>	IΡ	c
$ \vee $	20	6

Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.

UT Spot Track Ø86 GA Dali Version





Holding ring 08.8410.00 Screening crosspiece 08.8411.00