



## UT Spot Track Ø86 GA Dali Version

09.7750.30ADA - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated. .30 versions come with the track adapter, the arm and the rear of the head in black.

### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 2650   |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 29W   | Environment    | Indoor |
| CCT (K)         | 3000K |                |        |
| CRI             | 80    |                |        |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 12        |
| Beam angle C90-270 (°) | 12        |




Beam Angle: 12°

h(m) E(lx) D(m)

|   |       |      |
|---|-------|------|
| 1 | 34142 | 0.21 |
| 2 | 8535  | 0.41 |
| 3 | 3794  | 0.62 |
| 4 | 2134  | 0.82 |
| 5 | 1366  | 1.03 |

Luminous flux luminaire  
2650 lm




### Electrical

|                |                             |                  |    |
|----------------|-----------------------------|------------------|----|
| Frequency (Hz) | 50/60                       | Insulation class | II |
| Dimmable       | Yes                         |                  |    |
| Driver         | Integrated                  |                  |    |
| Driver type    | Electronic<br>dimmable DALI |                  |    |
| Emergency      | Without                     |                  |    |

### Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | White      | Spot diameter (mm) | 86 |
| Orientation  | Adjustable |                    |    |
| Weight (kg)  | 0.75       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

### Certification / Marking



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.

UT Spot Track Ø86 GA Dali Version



Holding ring  
08.8410.00



Screening crosspiece  
08.8411.00



Elliptical lens  
08.8163.68



Flood lens  
08.8175.68



Honeycomb  
08.8495.14