



## UT Spot Track Ø86 GA Dali Version All White

09.7751.30AYU - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 2281   |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 29W   | Environment    | Indoor |
| CCT (K)         | 4000K |                |        |
| CRI             | 90    |                |        |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 12        |
| Beam angle C90-270 (°) | 12        |



Beam Angle: 12°

h(m) E(lx) D(m)

1 29396 0.21

2 7349 0.41

3 3266 0.62

4 1837 0.82

5 1176 1.03

Luminous flux luminaire  
2281 lm

### Electrical


|                |                             |                  |    |
|----------------|-----------------------------|------------------|----|
| Frequency (Hz) | 50/60                       | Insulation class | II |
| Dimmable       | Yes                         |                  |    |
| Driver         | Integrated                  |                  |    |
| Driver type    | Electronic<br>dimmable DALI |                  |    |
| Emergency      | Without                     |                  |    |

### Physical


|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | White      | Spot diameter (mm) | 86 |
| Orientation  | Adjustable |                    |    |
| Weight (kg)  | 0.75       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.



### Certification / Marking



UT Spot Track Ø86 GA Dali Version All White



Holding ring  
08.8410.00



Screening crosspiece  
08.8411.00



Elliptical lens  
08.8163.68



Flood lens  
08.8175.68



Honeycomb  
08.8495.14