

## UT Spot Track Ø86 On Board Dimmer Included

09.4243.30 - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

Number of heads	1	Net lumen (lm)	1822
Lamp category	LED	Mountings	Track
Power (W)	34.1W	Environment	Indoor
CCT (K)	3000K		
CRI	98		

### Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle: 16°

h(m)	E(lx)	D(m)
1	12488	0.28
2	3122	0.55
3	1388	0.83
4	781	1.10
5	500	1.38

Luminous flux luminaire  
1648 lm


### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable		

### Physical

Color	White
Orientation	Adjustable
Weight (kg)	1.36
Tilt (°)	90
Rotation (°)	360

### Certification / Marking



### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø86 On Board Dimmer Included



---

Holding ring  
08.8410.00

---

Screening crosspiece  
08.8411.00