

UT Spot Track Ø86 On Board Dimmer Included

09.4250.30 - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 2216 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 29.3W | Environment | Indoor |
| CCT (K) | 4000K | | |
| CRI | 80 | | |

Optical

| | |
|------------------------|--------------|
| Lighting type | Direct |
| LED type | Phosphor LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 17 |
| Beam angle C90-270 (°) | 17 |



Beam Angle: 17°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 16217 | 0.29 |
| 2 | 4054 | 0.58 |
| 3 | 1802 | 0.88 |
| 4 | 1014 | 1.17 |
| 5 | 649 | 1.46 |

Luminous flux luminaire
2216 lm


Electrical

| | | | |
|----------------|---------------------|------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Electronic dimmable | | |
| Emergency | Without | | |

Physical

| | |
|--------------|------------|
| Color | White |
| Orientation | Adjustable |
| Weight (kg) | 1.36 |
| Tilt (°) | 90 |
| Rotation (°) | 360 |

Certification / Marking



Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

UT Spot Track Ø86 On Board Dimmer Included



Holding ring
08.8410.00

Screening crosspiece
08.8411.00