

## UT Spot Track Wall-Washer Ø 86

■ 09.4957.14A - Black


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2204
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	33W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		

### Optical

<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wall-washer
<b>Beam angle (°)</b>	50
<b>Beam angle C90-270 (°)</b>	56



<b>Beam Angle:</b>	50°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2236	0.98	
2	559	1.97	
3	248	2.95	
4	140	3.94	
5	89	4.92	

Luminous flux luminaire  
2204 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	1.55
<b>Tilt (°)</b>	90
<b>Rotation (°)</b>	360

### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.

