



## UT Spot Track Wall-Washer Ø 86 Dali Version

■ 09.4956.30ADA - White


Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	2204
<b>Power (W)</b>	32.8	<b>Mountings</b>	Track
<b>System power (W)</b>	32.8	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		


### Optical

<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wall Washer
	Down
<b>Beam angle (°)</b>	50
<b>Beam angle C90-270 (°)</b>	56



<b>Beam Angle: 50°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	2236	0.98
2	559	1.97
3	248	2.95
4	140	3.94
5	89	4.92

Luminous flux luminaire  
2204 lm



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Driver type</b>	Dimmable DALI 1
<b>Voltage (V)</b>	220-240V	<b>Emergency</b>	Without
<b>Current (mA)</b>	900	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	86
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	1.18		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		



### Note

FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.