



## UT Spot Track Wall-Washer Ø 86 GA

09.7770.30A - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated. .30 versions come with the track adapter, the arm and the rear of the head in black.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2560
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	33W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wall Washer
	Down
<b>Beam angle (°)</b>	50
<b>Beam angle C90-270 (°)</b>	50



<b>Beam Angle:</b>	50°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2596	0.98	
2	649	1.97	
3	288	2.95	
4	162	3.94	
5	104	4.92	

Luminous flux luminaire  
2560 lm



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	86
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	1.55		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.