

UT Spot Track Wall-Washer Ø86 GA

■ 09.7772.14A - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated.

Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 2204 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 33W | Environment | Indoor |
| CCT (K) | 4000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-------------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Wall-washer |
| Beam angle (°) | 50 |
| Beam angle C90-270 (°) | 50 |



Beam Angle: 50°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 2236 | 0.98 |
| 2 | 559 | 1.97 |
| 3 | 248 | 2.95 |
| 4 | 140 | 3.94 |
| 5 | 89 | 4.92 |

Luminous flux luminaire
2204 lm


Electrical

| | | | |
|----------------|------------|------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Electronic | | |
| Emergency | Without | | |

Physical

| | | | |
|--------------|------------|--------------------|----|
| Color | Black | Spot diameter (mm) | 86 |
| Orientation | Adjustable | | |
| Weight (kg) | 1.55 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Certification / Marking



Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.