



## UT Spot Track Wall-Washer Ø86 GA Dali Version

09.7771.30ADA - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply integrated. .30 versions come with the track adapter, the arm and the rear of the head in black.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2116
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	29W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wall-washer
<b>Beam angle (°)</b>	50
<b>Beam angle C90-270 (°)</b>	50



Beam Angle: 50°

h(m)	E(lx)	D(m)
1	2146	0.98
2	537	1.97
3	238	2.95
4	134	3.94
5	86	4.92

Luminous flux luminaire  
2116 lm




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic dimnable DALI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	86
<b>Orientation</b>	Adjustable		
<b>Weight (kg)</b>	1.55		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Certification / Marking



### Note

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request. FLOS three-phase DALI track luminaires are designed for Pulse DALI from Nordic Aluminium.