


Wall System Back 1 Power Supply Integrated Optical Switch

■ F9497057 - Chrome

Indirect-illumination lighting device for wall mounting with integrated driver and with round ornamental (ø125). ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

Indirect-illumination lighting device for wall mounting with integrated driver and with round ornamental (ø125). ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).




Main specifications

Number of heads	1	Net lumen (lm)	269
Lamp category	LED	Mountings	Wall surface
Power (W)	6W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

LED type	Top LED
Light distribution	Asymmetric
Optical type	Wide flood
Beam angle (°)	70



Beam Angle: 70°		
h(m)	E(lx)	D(m)
1	148	2.05
2	37	4.10
3	16	6.16
4	9	8.21
5	6	10.26


Luminous flux luminaire
269 lm

Electrical

Frequency (Hz)	50/60	Insulation class	III
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable		
Emergency	Without		

Physical

Color	Chrome
Orientation	Adjustable
Weight (kg)	0.42



Wall System Back 1 Power Supply Integrated Optical Switch



3-module flush mounted box for Pladur
80.8006



3-module flush mounted box for
masonry
80.8067