

## Wall System Back 1 Power Supply Integrated Optical Switch

■ F9497057 - Chrome

Indirect-illumination lighting device for wall mounting with integrated driver and with round ornamental (ø125). ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

Indirect-illumination lighting device for wall mounting with integrated driver and with round ornamental (ø125). ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	269
<b>Lamp category</b>	LED	<b>Mountings</b>	Wall surface
<b>Power (W)</b>	6W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		

### Optical

<b>LED type</b>	Top LED
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	70



Beam Angle:	70°		
	h(m)	E(lx)	D(m)
1	148	2.05	
2	37	4.10	
3	16	6.16	
4	9	8.21	
5	6	10.26	


Luminous flux luminaire  
269 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Chrome
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.42



## Wall System Back 1 Power Supply Integrated Optical Switch



---

3-module flush mounted box for Pladur  
80.8006



---

3-module flush mounted box for  
masonry  
80.8067