

Wall System Back 1 Remote Power Supply Optical Switch

■ F9493057 - Chrome

Indirect-illumination lighting device for installation flush with the wall with remote driver. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% – 50% – 0%).

Indirect-illumination lighting device for installation flush with the wall with remote driver. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 269 |
| Lamp category | LED | Mountings | Wall surface |
| Power (W) | 6W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 80 | | |

Optical

| | |
|--------------------|------------|
| LED type | Top LED |
| Light distribution | Asymmetric |
| Optical type | Wide flood |
| Beam angle (°) | 91 |



Luminous flux luminaire
269 lm

Beam Angle: 91°



| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 148 | 2.05 |
| 2 | 37 | 4.10 |
| 3 | 16 | 6.16 |
| 4 | 9 | 8.21 |
| 5 | 6 | 10.26 |

Electrical

| | | | |
|----------------|----------|------------------|-----|
| Frequency (Hz) | 50/60 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Dimmable | | |
| Emergency | Without | | |

Physical


| | |
|-------------|------------|
| Color | Chrome |
| Orientation | Adjustable |
| Weight (kg) | 0.30 |



Wall System Back 1 Remote Power Supply Optical Switch



Electronic transformer with constant
voltage (24V) for LED. 8W, 220/240V,
50/60H
60.8079



Electronic transformer with constant
voltage (24V) for LED. 8W, 110/240V,
50/60H
60.9157