

Wall System Minikelvin Flex Power Supply Integrated

■ F9463030 - Black

Diffuse illumination lighting device for installation flush with the wall with integrated driver and with round ornamental (ø125). ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% – 50% – 0%).


Diffuse illumination lighting device for installation flush with the wall with integrated driver and with round ornamental (ø125). ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% – 50% – 0%).

Main specifications

Number of heads	1	Net lumen (lm)	96
Lamp category	LED	Mountings	Wall surface
Power (W)	4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	85		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	111



Beam Angle: 111°

h(m) E(lx) D(m)

1 36 2.89

2 9 5.77

3 4 8.66

4 2 11.55

5 1 14.44



Luminous flux luminaire
96 lm

Electrical

Frequency (Hz)	50/60	Insulation class	III
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable		
Emergency	Without		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.40



Wall System Minikelvin Flex Power Supply Integrated



3-module flush mounted box for Pladur
80.8006



3-module flush mounted box for
masonry
80.8067