

## Wallee Casambi

New

03.8091.40.CB - White


Lighting LED module to be installed in The Tracking Magnet System.

## Main specifications

Lamp category	LED	Net lumen (lm)	446
Power (W)	10W	Mountings	Track
System power (W)	9.3	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

## Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	100
Beam angle C90-270 (°)	100
Efficiency (lm/W)	47.96



Beam Angle: 103°

h(m)	E(lx)	D(m)
1	169	2.50
2	42	5.00
3	19	7.49
4	11	9.99
5	7	12.49

Luminous flux luminaire  
446 lm

## Electrical

Voltage (V)	48	Emergency	Without
Current (mA)	180	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		

## Physical

Color	White	Length (mm)	242
Orientation	Adjustable	Lifespan (L70 B10)	L80B50
Weight (kg)	0.22		
Tilt (°)	25		
Rotation (°)	25		

## Note

When installing Wallee, it may require a manual adjustment by the client/installer. Find information on how to carry out this adjustment in the instruction sheets. Only allowed with Tracking Magnet Recessed and horizontal installation. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

