

Wallee Dali Version

03.8090.40.DA - White

Lighting LED module to be installed in The Tracking Magnet System.




Main specifications

Lamp category	LED	Mountings	Track
Power (W)	10W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		
Net lumen (lm)	413		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	100
Beam angle C90-270 (°)	100



Beam Angle: 103°

	h(m)	E(lx)	D(m)
1	164	2.50	
2	41	5.00	
3	18	7.49	
4	10	9.99	
5	7	12.49	

Luminous flux luminaire
431 lm



Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI 1		
Emergency	Without		

Physical

Color	White	Length (mm)	242
Orientation	Adjustable		
Weight (kg)	0.22		
Tilt (°)	25		
Rotation (°)	25		

Note

When installing Wallee, it may require a manual adjustment by the client/installer. Find information on how to carry out this adjustment in the instruction sheets. Only allowed with Tracking Magnet Recessed and horizontal installation. Only compatible with DALI profile version.

