



Wallee Dali Version

■ 03.8091.14.DA - Black

Lighting LED module to be installed in The Tracking Magnet System.

Main specifications

 Lamp category
 LED

 Power (W)
 10W

 System power (W)
 9.3

 CCT (K)
 3000K

 CRI
 90

Net lumen (lm) 465 Mountings Track

Environment Indoor dry location

Optical

Lighting type

LED type

Light distribution

Optical type

Beam angle (°)

Beam angle C90-270 (°)

Efficiency (Im/W)

Direct

Top LED


Symmetric

Diffused light

100

100

50



Luminous flux luminaire 446 lm

Beam Angle:		103°
h(m)	E(lx)	D(m
1	169	2.50
2	42	5.00
3	19	7.49
4	11	9.99
5	7	12 //

Electrical

 Voltage (V)
 48

 Current (mA)
 190

 Dimmable
 Yes

 Driver
 Remote excluded

 Driver type
 Dimmable DALI

Emergency Without Insulation class

Physical

Rotation (°)

Color Black Length (mm) 242
Orientation Adjustable Lifespan (L70 B10) L80B50
Weight (kg) 0.22
Tilt (°) 25

25

Note

When installing Wallee, it may require a manual adjustment by the client/installer. Find information on how to carry out this adjustment in the instruction sheets. Only allowed with Tracking Magnet Recessed and horizontal installation. Only compatible with DALI profile version.