

Wallee Dimmable 1-10V

■ 03.8090.14.1V - Black


Lighting LED module to be installed in The Tracking Magnet System.

**Main specifications**

Lamp category	LED	Net lumen (lm)	413
Power (W)	9.3W	Mountings	Track
System power (W)	9.3	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	100
Beam angle C90-270 (°)	100
Efficiency (lm/W)	44.41



Beam Angle: 103°

h(m)	E(lx)	D(m)
1	164	2.50
2	41	5.00
3	18	7.49
4	10	9.99
5	7	12.49

Luminous flux luminaire
431 lm**Electrical**

Voltage (V)	48	Emergency	Without
Current (mA)	190	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable 1-10V		

Physical

Color	Black	Length (mm)	242
Orientation	Adjustable	Lifespan (L70 B10)	L80B50
Weight (kg)	0.22		
Tilt (°)	25		
Rotation (°)	25		

Note

When installing Wallee, it may require a manual adjustment by the client/installer. Find information on how to carry out this adjustment in the instruction sheets. Only allowed with Tracking Magnet Recessed and horizontal installation. Only compatible with 1-10V profile version.

