



Wan Spot

03.6174.GNA - Green


Spotlight to be installed recessed on ceiling/wall. Power supply not included.

Main specifications

Number of heads	1	Net lumen (lm)	505
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	83
Beam angle C90-270 (°)	83



Beam Angle: 82°

h(m)	E(lx)	D(m)
1	362	1.75
2	91	3.50
3	40	5.25
4	23	7.00
5	14	8.75

Luminous flux luminaire
505 lm




Electrical

Frequency (Hz)	50/60	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		
Emergency	Without		

Physical

Color	Green	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	50		
Weight (kg)	0.50		
Tilt (°)	60		



Wan Spot



Continuous current power supply of 25W, 110/240V – 50/60Hz with power current selected through adjustable 350 mA-18W / 400 mA – 21W / 500mA – 25W /600mA – 30W /700/750/900 mA – 32W switch. 1-10V or push dimming, synchronisation cables not included.
60.8533

Continuous current power supply. 230/240V – 50/60Hz. Adjustable Current 350mA – 17W / 500mA – 24W / 700/ 750 mA – 32W switch by trailing and leading edge dimming, mains dimming or push dimming
60.8534

Not dimmable continuous current power supply. 20W, 500 mA – 110/240V – 50/60Hz
60.8650



Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W /400 mA – 17W /450 mA – 19W /500/550/600/700 mA – 20W, Dali 1 switch.
60.8847