

## Zero Track Surface Profile

06.2500.40 - White

Electro-mechanical indoor profile for surface installation (ceiling or wall). To be fixed with specific screw plugs that come with the profile.

### Main specifications

Mountings	Surface
Environment	Indoor dry location

### Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

### Physical

Color	White
Weight (kg)	0.21
Length (mm)	1000

### Note

It is necessary to order the power connector, intermediate connectors and covers separately. Feed unit connectors available as 90° flat corner and curve (symmetric element for left/right corner), ceiling/wall - wall/wall inner corner, as well as "T" and "X" shape. For vertical installations, installing the stopper is mandatory. It must be ordered separately.

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



## Zero Track Surface Profile



Power supply surface middle. 57W –  
220/240V  
06.2511.14



Zero Track Surface Profile. Feed  
intermediate connector  
06.2541.14



Zero Track Surface Profile. T-shaped  
connector  
06.2545.18



24V Remote power supply. Dimmable  
through DALI protocol. 120W 110/240V  
60.9426



Zero Track Surface Profile.  
Intermediate Connector  
06.2506.40



Zero Track Surface Profile. Cross-  
shaped connector  
06.2546.18



24V Remote power supply. Dimmable  
through 1/10V protocol. 120W 110/240V  
60.9416



Zero Track Surface Profile. Ceiling/wall  
– wall/wall inner corner  
06.2543.18



Zero Track Surface Profile. 90° Flat  
Corner  
06.2542.40




Power supply surface middle. 57W – 220/240V  
06.2511.06



Zero Track Surface Profile. T-shaped connector  
06.2545.14



Zero Track Surface Profile. Intermediate Connector  
06.2506.14




Zero Track Surface Profile. Feed Unit for Remote Power Supply Unit  
06.2540.CZ



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V  
60.9359



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V  
60.9361



Zero Track Surface Profile. 90° Flat Corner  
06.2542.18



Power supply surface end. 57W – 220/240V  
06.2510.06




Zero Track Surface Profile. End Cap  
06.2509.40




---

Power supply surface middle. 57W –  
220/240V  
06.2511.40





---

Zero Track Surface Profile. T-shaped  
connector  
06.2545.40




---

Power supply surface middle. 57W –  
220/240V  
06.2511.18




---

Zero Track Surface Profile. Cross-  
shaped connector  
06.2546.40





---

Zero Track Surface Profile. Feed  
intermediate connector  
06.2541.18





---

Zero Track Surface Profile. Interior  
ceiling/ceiling-wall/wall curve  
06.2544.14




---

Zero Track Surface Profile. 90° Flat  
Corner  
06.2542.CZ




---

Zero Track Surface Profile. End Cap  
06.2509.14





---

Zero Track Surface Profile. Interior  
ceiling/ceiling-wall/wall curve  
06.2544.40



Power supply surface end. 57W –  
220/240V  
06.2510.18



Zero Track Surface Profile. Feed  
intermediate connector  
06.2541.CZ



Zero Track Surface Profile. Feed Unit  
for Remote Power Supply Unit  
06.2540.14




Zero Track Surface Profile. Ceiling/wall  
– wall/wall inner corner  
06.2543.14



Remote Power Supply Non Dimmable  
24V. 120W. 220/240V  
60.9516



Power supply surface end. 57W –  
220/240V  
06.2510.14



Zero Track Surface Profile. T-shaped  
connector  
06.2545.CZ



Casambi Controller 220-240V. Remote  
Installation  
60.9392




Zero Track Surface Profile. Interior  
ceiling/ceiling-wall/wall curve  
06.2544.18



---

Power supply surface middle. 57W –  
220/240V  
06.2511.CZ



---

Zero Track Surface Profile. Feed  
intermediate connector  
06.2541.40



---

Power supply surface end. 57W –  
220/240V  
06.2510.CZ



---



Zero Track Surface Profile. Cross-  
shaped connector  
06.2546.14

---

Zero Track Surface Profile. Ceiling/wall  
– wall/wall inner corner  
06.2543.CZ

---

24V Remote power supply. Dimmable  
through 1/10V protocol or Non  
Dimmable. Dimming range 20-100%.  
36W-110V / 45W-240V  
60.9360



---


Zero Track Surface Profile. Interior  
ceiling/ceiling-wall/wall curve  
06.2544.CZ

---

Zero Track Surface Profile. 90° Flat  
Corner  
06.2542.14

---

Zero Track Surface Profile. Feed Unit  
for Remote Power Supply Unit  
06.2540.40






---

Power supply surface end. 57W –  
220/240V  
06.2510.40

---

Zero Track Surface Profile. Cross-  
shaped connector  
06.2546.CZ



---

Stopper  
08.0630.14



---

Zero Track Surface Profile. Feed Unit  
for Remote Power Supply Unit  
06.2540.18



---

Zero Track Surface Profile. Ceiling/wall  
– wall/wall inner corner  
06.2543.40