

Zero Track Surface Profile

06.2502.CZ - Bronze

Electro-mechanical indoor profile for surface installation (ceiling or wall). To be fixed with specific screw plugs that come with the profile.

Main specifications

Mountings	Surface
Environment	Indoor dry location

Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Bronze
Weight (kg)	0.62
Length (mm)	3000

Note

It is necessary to order the power connector, intermediate connectors and covers separately. Feed unit connectors available as 90° flat corner and curve (symmetric element for left/right corner), ceiling/wall - wall/wall inner corner, as well as "T" and "X" shape. For vertical installations, installing the stopper is mandatory. It must be ordered separately.

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



Zero Track Surface Profile



Zero Track Surface Profile.
Intermediate Connector
06.2506.40



Zero Track Surface Profile. Cross-
shaped connector
06.2546.18



Zero Track Surface Profile. T-shaped
connector
06.2545.14



Zero Track Surface Profile. 90° Flat
Corner
06.2542.40



Power supply surface middle. 57W –
220/240V
06.2511.06




Zero Track Surface Profile. Ceiling/wall
– wall/wall inner corner
06.2543.CZ



24V Remote power supply. Dimmable
through 1/10V protocol or Non
Dimmable. Dimming range 20-100%.
36W-110V / 45W-240V
60.9360




Zero Track Surface Profile.
Intermediate Connector
06.2506.14



Zero Track Surface Profile. Feed Unit
for Remote Power Supply Unit
06.2540.CZ



Power supply surface end. 57W –
220/240V
06.2510.CZ



Zero Track Surface Profile. Cross-
shaped connector
06.2546.14




Zero Track Surface Profile. End Cap
06.2509.40



Zero Track Surface Profile. Feed
intermediate connector
06.2541.18



Power supply surface middle. 57W –
220/240V
06.2511.18




Zero Track Surface Profile. Cross-
shaped connector
06.2546.40




Zero Track Surface Profile. Interior
ceiling/ceiling-wall/wall curve
06.2544.14



Zero Track Surface Profile. T-shaped
connector
06.2545.18



Zero Track Surface Profile. 90° Flat
Corner
06.2542.CZ



Zero Track Surface Profile. End Cap
06.2509.14



Zero Track Surface Profile. Feed
intermediate connector
06.2541.14



Zero Track Surface Profile. Ceiling/wall
– wall/wall inner corner
06.2543.18



Power supply surface middle. 57W –
220/240V
06.2511.14



Zero Track Surface Profile. Feed Unit
for Remote Power Supply Unit
06.2540.14




Zero Track Surface Profile. Ceiling/wall
– wall/wall inner corner
06.2543.14



24V Remote power supply. Dimmable
through 1/10V protocol. 120W 110/240V
60.9416



Power supply surface end. 57W –
220/240V
06.2510.14



Zero Track Surface Profile. T-shaped
connector
06.2545.CZ






Power supply surface middle. 57W – 220/240V
06.2511.CZ



Zero Track Surface Profile. Feed intermediate connector
06.2541.40



Casambi Controller 220-240V. Remote Installation
60.9392



Remote Power Supply Non Dimmable 24V. 120W. 220/240V
60.9516



Power supply surface end. 57W – 220/240V
06.2510.06



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V
60.9359



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V
60.9361



Zero Track Surface Profile. Interior ceiling/ceiling-wall/wall curve
06.2544.18




Power supply surface middle. 57W – 220/240V
06.2511.40





Zero Track Surface Profile. T-shaped connector
06.2545.40

Zero Track Surface Profile. 90° Flat Corner
06.2542.18



Zero Track Surface Profile. 90° Flat Corner
06.2542.14

24V Remote power supply. Dimmable through DALI protocol. 120W 110/240V
60.9426



Zero Track Surface Profile. Interior ceiling/ceiling-wall/wall curve
06.2544.CZ



Zero Track Surface Profile. Feed Unit for Remote Power Supply Unit
06.2540.18

Zero Track Surface Profile. Ceiling/wall – wall/wall inner corner
06.2543.40


Power supply surface end. 57W – 220/240V
06.2510.40



Zero Track Surface Profile. Feed Unit
for Remote Power Supply Unit
06.2540.40

Stopper
08.0630.14

Power supply surface end. 57W –
220/240V
06.2510.18



Zero Track Surface Profile. Feed
intermediate connector
06.2541.CZ

Zero Track Surface Profile. Cross-
shaped connector
06.2546.CZ

Zero Track Surface Profile. Interior
ceiling/ceiling-wall/wall curve
06.2544.40