

Zero Track Surface Profile. 90° Flat Corner

New

06.2542.18 - Deep Brown

90° flat corner. Can be powered. It has a rear space for the supply connection.



Main specifications

Mountings	Surface
Environment	Indoor dry location

Electrical


Voltage (V)	24.00
Emergency	Without
Insulation class	III

Physical

Color	Deep Brown
Weight (kg)	0.01
Length (mm)	75

Note

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



Zero Track Surface Profile. 90° Flat Corner



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V
60.9361

Remote Power Supply Non Dimmable 24V. 120W. 220/240V
60.9516

24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V
60.9359



24V Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V
60.9416

Casambi Controller 220-240V. Remote Installation
60.9392

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.
60.9352



24V Remote power supply. Dimmable

24V Remote power supply. Dimmable

36W-110V / 45W-240V
60.9360