

Zero Track Surface Profile. Ceiling/wall - wall/wall inner corner

New

06.2543.40 - White

Ceiling/wall - wall/wall inner corner. Can be powered. It has two spaces for the supply connection located on each side at the rear.

Ceiling/wall - wall/wall inner corner. Can be powered. It has two spaces for the supply connection located on each side at the rear.

Main specifications

Mountings	Surface
Environment	Indoor dry location

Electrical


Voltage (V)	24
Emergency	Without
Insulation class	III

Physical


Color	White
Weight (kg)	0.01
Length (mm)	76

Note

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



Zero Track Surface Profile. Ceiling/wall - wall/wall inner corner



Casambi Controller 220-240V. Remote Installation
60.9392



24V Remote power supply. Dimmable through DALI protocol. 120W 110/240V
60.9426



24V Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V
60.9416



Remote Power Supply Non Dimmable
24V. 120W. 220/240V
60.9516



LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.
60.9352



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V
60.9359



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V
60.9359



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V
60.9359

36W-110V / 45W-240V
60.9360