

Zero Track Surface Profile. Ceiling/wall - wall/wall inner corner

New

06.2543.CZ - Bronze

Ceiling/wall - wall/wall inner corner. Can be powered. It has two spaces for the supply connection located on each side at the rear.

Ceiling/wall - wall/wall inner corner. Can be powered. It has two spaces for the supply connection located on each side at the rear.

Main specifications

Mountings	Surface
Environment	Indoor dry location

Electrical


Voltage (V)	24
Emergency	Without
Insulation class	III

Physical


Color	Bronze
Weight (kg)	0.01
Length (mm)	76

Note

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



Zero Track Surface Profile. Ceiling/wall - wall/wall inner corner



Casambi Controller 220-240V. Remote Installation
60.9392



Remote Power Supply Non Dimmable
24V. 120W. 220/240V
60.9516



LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.
60.9352



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V
60.9359



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. Dimming range 20-100%. 36W-110V / 45W-240V
60.9360



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V
60.9361



60.9426

60.9416