

## Zero Track Surface Profile. Cross-shaped connector

New

06.2546.18 - White

Cross-shaped connector. Can be powered via connections on the back.

### Main specifications

Mountings	Surface
Environment	Indoor dry location

### Electrical


Voltage (V)	24
Emergency	Without
Insulation class	III

### Physical

Color	White
Weight (kg)	0.01
Length (mm)	76

### Note

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



Zero Track Surface Profile. Cross-shaped connector



24V Remote power supply. Dimmable through DALI protocol. 120W 110/240V  
60.9426



24V Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V  
60.9416



Casambi Controller 220-240V. Remote Installation  
60.9392



LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.  
60.9352



Remote Power Supply Non Dimmable 24V. 120W. 220/240V  
60.9516



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V  
60.9359



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V  
60.9359



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V  
60.9359

36W-110V / 45W-240V  
60.9360